

Universal Full-Size Truck Bench Seat Cover Installation Instructions
Fits 1947-98 Chevy/GMC, 1972-93 Dodge and 1947-91 Ford

Please read completely before beginning installation.

1. Tie a string to the loops on the top of the back rest and to either the front or rear loops of the seat bottom.
 2. Back Rest - Lay the cover over the seat, fit the top of the back rest making sure the top corners of the back rest are fitting correctly.
 3. Push in the middle where the seat bottom meets the seat back and feed the seat belts through the openings in the seat bottom.
 4. Locate the loops on the opposite side of the back rest. Tie the strings from the center loops top and bottom working from the center out to both sides. Don't tie the strings in a knot until you're sure the cover looks good and the front pockets are in the correct position on the seat bottom.
 5. Seat bottom - Feed the strings already tied earlier through the loops on the front or back side and secure the cover to the seat bottom starting from the center and working out to each side.
 6. Lastly, tie a string through the loops on the side of the seat cover and secure to another loop or bracket or wire in the seat frame.
- Note:** Make sure the strings don't interfere with the seat brackets so the seat back rest can fold forward and back without any problems. A little stretching of the strings is OK.

If the seat cover is in a bind, **Do Not Pull**. Work each side evenly until you can continue with the installation.