



INSTALLATION INSTRUCTIONS

MOROSO PART #22016 - SCREW-IN RESTRICTORS FOR SMALL & BIG BLOCK CHEVROLETS

NOTE: These Screw-in Restrictors are not be used with Hydraulic Lifters.

To install the Oil Restrictors, remove the two 1/4" pipe plugs from the lifter gallery at the back of the block. Brush the pipe thread on the Oil Screw Oil Restrictors with Felpo Pipe Sealer with Teflon (PST) or similar to prevent oil leaks. Screw Oil Restrictors into the block. After installing the Restrictors check for interference with motor plates, fly wheel or pressure plate bolts.

NOTE: When installing the Screw-In Oil Restrictors with a small block Chevy or a big block Chevy, the lifter gallery that intersects with the distributor hole should be carefully noted. The end of the Oil Restrictors should be almost flush with the entrance into the distributor shaft hole but should not extend into the hole. Due to the tolerances of the block and the pipe thread, it may be necessary to compensate for the depth of the Oil Restrictor by wrapping the pipe threads with Teflon tape.

PARTS LIST

- 2 Oil Restrictors
- 4 "O" Rings (2 spares)

**For Technical Assistance, Call Moroso's Tech Line
at**

(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437-2116
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At www.moros.com

Rev. A
061704

22016INST



INSTALLATION INSTRUCTIONS

MOROSO PART #22016 - SCREW-IN RESTRICTORS FOR SMALL & BIG BLOCK CHEVROLETS

NOTE: These Screw-in Restrictors are not be used with Hydraulic Lifters.

To install the Oil Restrictors, remove the two 1/4" pipe plugs from the lifter gallery at the back of the block. Brush the pipe thread on the Oil Screw Oil Restrictors with Felpo Pipe Sealer with Teflon (PST) or similar to prevent oil leaks. Screw Oil Restrictors into the block. After installing the Restrictors check for interference with motor plates, fly wheel or pressure plate bolts.

NOTE: When installing the Screw-In Oil Restrictors with a small block Chevy or a big block Chevy, the lifter gallery that intersects with the distributor hole should be carefully noted. The end of the Oil Restrictors should be almost flush with the entrance into the distributor shaft hole but should not extend into the hole. Due to the tolerances of the block and the pipe thread, it may be necessary to compensate for the depth of the Oil Restrictor by wrapping the pipe threads with Teflon tape.

PARTS LIST

- 2 Oil Restrictors
- 4 "O" Rings (2 spares)

**For Technical Assistance, Call Moroso's Tech Line
at**

(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437-2116
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At www.moros.com

Rev. A
061704

22016INST



INSTALLATION INSTRUCTIONS

MOROSO PART #22016 - SCREW-IN RESTRICTORS FOR SMALL & BIG BLOCK CHEVROLETS

NOTE: These Screw-in Restrictors are not be used with Hydraulic Lifters.

To install the Oil Restrictors, remove the two 1/4" pipe plugs from the lifter gallery at the back of the block. Brush the pipe thread on the Oil Screw Oil Restrictors with Felpo Pipe Sealer with Teflon (PST) or similar to prevent oil leaks. Screw Oil Restrictors into the block. After installing the Restrictors check for interference with motor plates, fly wheel or pressure plate bolts.

NOTE: When installing the Screw-In Oil Restrictors with a small block Chevy or a big block Chevy, the lifter gallery that intersects with the distributor hole should be carefully noted. The end of the Oil Restrictors should be almost flush with the entrance into the distributor shaft hole but should not extend into the hole. Due to the tolerances of the block and the pipe thread, it may be necessary to compensate for the depth of the Oil Restrictor by wrapping the pipe threads with Teflon tape.

PARTS LIST

- 2 Oil Restrictors
- 4 "O" Rings (2 spares)

**For Technical Assistance, Call Moroso's Tech Line
at**

(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437-2116
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At www.moros.com

Rev. A
061704

22016INST