



## **INSTALLATION INSTRUCTIONS**

**P/N 22662**

### **3-1/2 GALLON IVAK TRACK DRY SUMP TANK**

#### **PARTS LIST**

1- Lid and Baffle Assembly  
1- Lid Clamp  
1- Drain Plug  
1- 6AN Cap

1- Tank  
2- Square O-Rings  
1- Can Cap  
1 Small Drain Plug O-Ring

#### **INSTALLATION**

Place the O-ring on the underside of the lid. A small amount of heavy grease (Wheel bearing grease or equivalent) will hold the O-Ring to the lid. Slide the lid, O-ring and baffle assembly down into the tank, being careful not to lose the O-ring.

Using the lid clamp, fasten the lid to the tank. Tighten the clamp only enough to compress the O-ring to prevent leakage at the seam.

All threaded fittings are male –AN type, except the 3/4-16 drain plug. The lid dipstick hole is –6AN and the inlets and outlet are both –16AN.

**NOTE:** An extra O-ring has been provided as a replacement in case you damage the first one.

To check the oil level, remove –6AN cap and use the dipstick. The hole in the dipstick marks the recommended oil level.

**For Technical Assistance, Call Moroso's Tech Line at  
(203) 458-0542, 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC  
80 CARTER DR • GUILFORD, CT 06437-2116  
Phone: (203) 453-6571 • Fax: (203) 453-6906