



OIL FILTER BLOCK-OFF PLATE P/N 23780

NOTE: This plate is designed to be used **ONLY** with a dry sump oiling system. It will fit both Small and Big Block Chevrolets without any modification.

Before installing this plate, be sure to remove oil filter by-pass assembly and make sure all surfaces are thoroughly cleaned. Be sure to put a few drops of oil under bolt head, on bolt threads, and on O-ring washer. While tightening bolt snugly (25-30 ft./lbs.), be sure large O-ring stays in place and does not get squeezed out!

The threaded opening is 1/2" NPT. If you use a -10AN line, you need a #2021-8-10S aeroquip or equivalent fitting. If you use a -12AN line, a #2021-8-12S fitting will be required.

Remember to check for leaks upon fire-up. To prevent seepage from threaded opening, we recommend Teflon tape or equivalent be used on threads of fitting.

PARTS LIST:

- | | |
|---|------------------------------------|
| 1 | 1/2-13 X 3 HHCS GR5 CLEAR ZINC |
| 1 | O-RING, SQUARE, OIL FILTER BY-PASS |
| 1 | PLATE S&BBC OIL BKOFF |
| 1 | O-RING WASHER |

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am - 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At www.moroso.com

23780INST

Rev. B
071211



OIL FILTER BLOCK-OFF PLATE P/N 23780

NOTE: This plate is designed to be used **ONLY** with a dry sump oiling system. It will fit both Small and Big Block Chevrolets without any modification.

Before installing this plate, be sure to remove oil filter by-pass assembly and make sure all surfaces are thoroughly cleaned. Be sure to put a few drops of oil under bolt head, on bolt threads, and on O-ring washer. While tightening bolt snugly (25-30 ft./lbs.), be sure large O-ring stays in place and does not get squeezed out!

The threaded opening is 1/2" NPT. If you use a -10AN line, you need a #2021-8-10S aeroquip or equivalent fitting. If you use a -12AN line, a #2021-8-12S fitting will be required.

Remember to check for leaks upon fire-up. To prevent seepage from threaded opening, we recommend Teflon tape or equivalent be used on threads of fitting.

PARTS LIST:

- | | |
|---|------------------------------------|
| 1 | 1/2-13 X 3 HHCS GR5 CLEAR ZINC |
| 1 | O-RING, SQUARE, OIL FILTER BY-PASS |
| 1 | PLATE S&BBC OIL BKOFF |
| 1 | O-RING WASHER |

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am - 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At www.moroso.com

23780INST

Rev.B
071211



OIL FILTER BLOCK-OFF PLATE P/N 23780

NOTE: This plate is designed to be used **ONLY** with a dry sump oiling system. It will fit both Small and Big Block Chevrolets without any modification.

Before installing this plate, be sure to remove oil filter by-pass assembly and make sure all surfaces are thoroughly cleaned. Be sure to put a few drops of oil under bolt head, on bolt threads, and on O-ring washer. While tightening bolt snugly (25-30 ft./lbs.), be sure large O-ring stays in place and does not get squeezed out!

The threaded opening is 1/2" NPT. If you use a -10AN line, you need a #2021-8-10S aeroquip or equivalent fitting. If you use a -12AN line, a #2021-8-12S fitting will be required.

Remember to check for leaks upon fire-up. To prevent seepage from threaded opening, we recommend Teflon tape or equivalent be used on threads of fitting.

PARTS LIST:

- | | |
|---|------------------------------------|
| 1 | 1/2-13 X 3 HHCS GR5 CLEAR ZINC |
| 1 | O-RING, SQUARE, OIL FILTER BY-PASS |
| 1 | PLATE S&BBC OIL BKOFF |
| 1 | O-RING WASHER |

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am - 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At www.moroso.com

23780INST

Rev. B
071211



OIL FILTER BLOCK-OFF PLATE P/N 23780

NOTE: This plate is designed to be used **ONLY** with a dry sump oiling system. It will fit both Small and Big Block Chevrolets without any modification.

Before installing this plate, be sure to remove oil filter by-pass assembly and make sure all surfaces are thoroughly cleaned. Be sure to put a few drops of oil under bolt head, on bolt threads, and on O-ring washer. While tightening bolt snugly (25-30 ft./lbs.), be sure large O-ring stays in place and does not get squeezed out!

The threaded opening is 1/2" NPT. If you use a -10AN line, you need a #2021-8-10S aeroquip or equivalent fitting. If you use a -12AN line, a #2021-8-12S fitting will be required.

Remember to check for leaks upon fire-up. To prevent seepage from threaded opening, we recommend Teflon tape or equivalent be used on threads of fitting.

PARTS LIST:

- | | |
|---|------------------------------------|
| 1 | 1/2-13 X 3 HHCS GR5 CLEAR ZINC |
| 1 | O-RING, SQUARE, OIL FILTER BY-PASS |
| 1 | PLATE S&BBC OIL BKOFF |
| 1 | O-RING WASHER |

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am - 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At www.moroso.com

23780INST

Rev. B
071211