



FABRICATED VALVE COVER INSTRUCTIONS

1). Gasket Rail notches should be checked against your particular head prior to running the engine. These notches may be modified easily with a die grinder.

2). For best gasket rail seal, we recommend using a Silicone or Steel Reinforced Gasket, available through; Moroso, Felpro, or Mr. Gasket.

Cylinder Head	Moroso V/C P/N	Gasket
SBF-SN95 Mustangs	68323	Felpro 1645 or Moroso 93060
SBF 289,302,351W	68325	Felpro 1645 or Moroso 93060
Buick/SBC	68331	Felpro 1638 (fiber only)
SBC-Splayed Valve	68332	Felpro 1641
BBC-Pro Stock	68333	Felpro 1630
Pontiac-Pro Stock	68334	Felpro 1634
SBC-Including 18°	68335	Felpro 1604 or Moroso 93020
BBF	68348	Felpro 1619 (Cork) or 1617 (Rubber)
BBF	68349	Felpro 1619 (Cork) or 1617 (Rubber)

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437-2116
Phone: (203) 453-6571 • Fax: (203) 453-6906