



Self Vulcanizing Tape PART #72038

Moroso Self Vulcanizing Tape consists of uncured silicone rubber which, when wrapped around itself, bonds to provide a weatherproof seal and extra protection against heat and voltage loss. Moroso Self Vulcanizing Tape stretches 300% and will easily conform to most shapes.

INSTALLATION

1. Thoroughly clean surface to which Moroso Self Vulcanizing Tape is being applied.
- NOTE: (Do not use solvents to clean area)**
2. Remove backing from roll, place end of roll below area needed to be covered. Pulling tightly, make a wrap around itself to hold tape in place.
3. Using the line in the middle of the tape roll as a guide, wind tape in a spiral fashion lining up the edge of the roll with the middle line on each wrap. Be certain to pull tightly on each wrap.
4. Wind the tape past covered area at least 2 IN. and wrap tape around itself on final wrap to ensure good seal.

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Rev.A
012808

Visit Us At www.moroso.com

72038INST



Self Vulcanizing Tape PART #72038

Moroso Self Vulcanizing Tape consists of uncured silicone rubber which, when wrapped around itself, bonds to provide a weatherproof seal and extra protection against heat and voltage loss. Moroso Self Vulcanizing Tape stretches 300% and will easily conform to most shapes.

INSTALLATION

1. Thoroughly clean surface to which Moroso Self Vulcanizing Tape is being applied.
- NOTE: (Do not use solvents to clean area)**
2. Remove backing from roll, place end of roll below area needed to be covered. Pulling tightly, make a wrap around itself to hold tape in place.
3. Using the line in the middle of the tape roll as a guide, wind tape in a spiral fashion lining up the edge of the roll with the middle line on each wrap. Be certain to pull tightly on each wrap.
4. Wind the tape past covered area at least 2 IN. and wrap tape around itself on final wrap to ensure good seal.

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Rev.A
012808

Visit Us At www.moroso.com

72038INST



Self Vulcanizing Tape PART #72038

Moroso Self Vulcanizing Tape consists of uncured silicone rubber which, when wrapped around itself, bonds to provide a weatherproof seal and extra protection against heat and voltage loss. Moroso Self Vulcanizing Tape stretches 300% and will easily conform to most shapes.

INSTALLATION

1. Thoroughly clean surface to which Moroso Self Vulcanizing Tape is being applied.
- NOTE: (Do not use solvents to clean area)**
2. Remove backing from roll, place end of roll below area needed to be covered. Pulling tightly, make a wrap around itself to hold tape in place.
3. Using the line in the middle of the tape roll as a guide, wind tape in a spiral fashion lining up the edge of the roll with the middle line on each wrap. Be certain to pull tightly on each wrap.
4. Wind the tape past covered area at least 2 IN. and wrap tape around itself on final wrap to ensure good seal.

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Rev.A
012808

Visit Us At www.moroso.com

72038INST



Self Vulcanizing Tape PART #72038

Moroso Self Vulcanizing Tape consists of uncured silicone rubber which, when wrapped around itself, bonds to provide a weatherproof seal and extra protection against heat and voltage loss. Moroso Self Vulcanizing Tape stretches 300% and will easily conform to most shapes.

INSTALLATION

1. Thoroughly clean surface to which Moroso Self Vulcanizing Tape is being applied.
- NOTE: (Do not use solvents to clean area)**
2. Remove backing from roll, place end of roll below area needed to be covered. Pulling tightly, make a wrap around itself to hold tape in place.
3. Using the line in the middle of the tape roll as a guide, wind tape in a spiral fashion lining up the edge of the roll with the middle line on each wrap. Be certain to pull tightly on each wrap.
4. Wind the tape past covered area at least 2 IN. and wrap tape around itself on final wrap to ensure good seal.

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Rev.A
012808

Visit Us At www.moroso.com

72038INST