


VEHICLE					PIONEER	CONNECTOR	HEIGHT ADDED mm / in	
FORD F250/350/450/550 Super Cab / Crew Cab Pickup/Ute 4 dr					62101	RLT600		
REGION	AUS	NZ	USA	CA	SA	UK	EU	ZA
AVAILABILITY	✓	✓	✓	✓	✗	✓	✓	✓
RUN DATES	2008 - 2016	2008 - 2016	2008 - 2016	2008 - 2016	-	2008 -	2008 -	2008 -
VEHICLE NOTES	- Do not operate sunroof							

VISIT THE ONLINE
CALCULATOR FOR
CURRENT SYSTEM
LOAD LIMIT DATA



DYNAMIC ROAD LOAD LIMIT (NOTE: DIFFERENT ON AND OFF ROAD CARGO LIMIT)
***USE THE VEHICLE MANUFACTURER'S MAXIMUM ROOF ALLOWANCE IF IT IS LOWER THAN THE FIGURE LISTED**

LOAD LIMIT

UP TO **100 Kg***
220 lbs

SYSTEM WEIGHT

UP TO **22 Kg**
48 lbs

=

ON ROAD CARGO LIMIT

UP TO **78 Kg**
172 lbs

OR

OFF ROAD CARGO LIMIT
(ON ROAD CARGO LIMIT / 1.5)

UP TO **52 Kg**
115 lbs

UNDERBAR SPACING

FRONT

+

REAR

BAR	A	B	C	D	E	F	G
DIMENSION (CM)	-28	0	52				
SPACERS REQ'D							
CONNECTOR	RLT600		RLT600				
OUTER UNDERBAR COVER (mm/in)	Refer to Step 11-12 in the Pioneer Series 6 Instructions to trim B and C						
CENTRE UNDERBAR COVER (mm/in)	Refer to Step 11-12 in the Pioneer Series 6 Instructions to trim A						

NOTES FOR DEALERS / FITTERS

It is your responsibility to ensure these fitting instructions are given to the end user or client.