



VEHICLE					PIONEER	CONNECTOR	HEIGHT ADDED mm / in	
KIA SPORTAGE NQ5 Gen 5 4WD-SUV Raised Rail 5dr					62109	RX2FK009	111 / 4.4	
REGION	AUS	NZ	USA	CA	SA	UK	EU	ZA
AVAILABILITY	✓	✓	✓	✓	✓	✗	✗	✗
RUN DATES	2021 -	2021 -	2022 -	2022 -	2022 -	-	-	-
VEHICLE NOTES	-							

VISIT THE ONLINE
CALCULATOR FOR
CURRENT SYSTEM
LOAD LIMIT DATA



DYNAMIC LOAD LIMIT (ON AND OFF-ROAD):
***USE THE VEHICLE MANUFACTURER'S MAXIMUM ROOF ALLOWANCE IF IT IS LOWER THAN THE FIGURE LISTED**



OR



UP TO **82 Kg**
180 lbs

+ **18 Kg**
40 lbs **=**


UP TO **100 Kg**
220 lbs

***VEHICLE
MANUFACTURER'S
ROOF LOAD LIMIT**



TOTAL STATIC LOAD LIMIT: UP TO 250 Kg / 551 lbs*

**PAD AND CLAMP
DETAILS**



FL

100-004-00369

100-006-00093

100-004-00370

FR

100-004-00369

100-006-00094

100-004-00370

RL

100-004-00369

100-006-00095

100-004-00371

RR

100-004-00369

100-006-00096

100-004-00371

UNDERBAR SPACING

FRONT

REAR

BAR	A	B	C	D	E	F	G
DIMENSION (CM)	-40	0	35				
SPACERS REQ'D							
CONNECTOR	RX2FK009		RX2FK009				
OUTER UNDERBAR COVER (mm/in)	Refer to Step 11-12 in the Pioneer Series 6 Instructions to trim B and C						
CENTRE UNDERBAR COVER (mm/in)	Refer to Step 11-12 in the Pioneer Series 6 Instructions to trim A						

NOTES FOR DEALERS / FITTERS

It is your responsibility to ensure these fitting instructions are given to the end user or client.