

Exhaust Tip Replacement Package, F-150, Dual Outlet

PACKING LIST

Before installation, use this check list to make sure all necessary parts have been included.

ITEM	QTY	CHECK	PART NUMBER	DESCRIPTION
1.	1	☐	310301853	Tip Assy, F-150, Dual Outlet, Replacement Tip
2.	1	☐	308144380	CLAMP, 2.5" Torca Band, Vette/Must/Cobra/W-Body/GTO
3.	1	☐	310011793	Adapter, 45 Degree, Silverado/Sierra, Cat-Back
4.	1	☐	308303902	Clamp, 2.5" Exhaust, Uni-Bolt
5.	1	☐	*****	Instructions

WARNING: SLP Recommends wearing safety glasses for the complete installation.

WARNING: SLP Recommends allowing the vehicle to cool (not running) for two hours before beginning installation.

INSTALLATION INSTRUCTIONS – #F31041

1. To install the tip replacement package the end section of your stock F-150 exhaust system needs to be cut off with a suitable cutoff tool or hacksaw.
2. Depending on your specific taste as to where the tip lands will dictate how much of your stock system you cut off. Here at SLP we have found that cutting off 20.5" from the end of the stock exhaust system along the centerline of the stock tube puts the end of the new SLP dual tip with adapter in a great location.
3. After you cut your stock exhaust use the unbolt style clamp to clamp the SLP adapter to the stock exhaust system and use the band clamp to attach the new dual tip to the end of the 45 degree adapter.
4. This completes your installation. ENJOY!