



151 INDUSTRIAL DRIVE
ASHLAND, MISSISSIPPI 38603
<http://www.tciauto.com>

TELEPHONE: 662-224-8972
FAX LINE: 662-224-8255
E-MAIL: tech@tciauto.com

TCI® 351073 Quick Release Starter Harness

This quick release harness is of a type that will adapt to most any original General Motors Harness. The color code, in most cases is the same as the OE, and should always be wired as such.

Note: Some G.M. vehicles have only two wires, the purple and pink wire, plus the battery cable. The TCI® 351073 is a three wire harness that can be adapted for a two wire application, simply cut the big red wire in locations marked on illustration (11 & 13) and discard if so desired. It is not necessary to remove this wire, you may simply tie it back out of the way. Important: When cutting the original harness make sure that you only use high quality connectors to connect your new quick release harness. Solder the ends and wrap each separately using electrical tape. This procedure is a Must to insure proper installation. Before installation is completed, check your battery to verify that it is putting out the proper amount of amperage and in good condition. Also, inspect the battery ends for good connections and replace cable ends if needed. Inspect your starter and flywheel, replace parts if necessary.

Refer to illustration:

The Purple wire is the solenoid wire - connect to the terminal marked "S" inside of solenoid (14)

The Pink wire is the resister wire - connect to the terminal marked "R" inside of solenoid (16)

The Red wire is the battery wire - connect to the battery terminal (15)

To operate the quick release, simply lift up on the tab, you will hear a click then hold each end and pull straight out. Do Not Pull By Wires!

