



TAIL LIGHTGUARD

Installation Instructions

PLEASE READ THESE INSTRUCTIONS BEFORE INSTALLATION

- 1) Hold TAIL LIGHTGUARD up to tail light and press in place to determine correct alignment.
- 2) Thoroughly clean mounting location with alcohol pad provided.
- 3) Peel backing from dual-lock and press firmly in place.
- 4) Avoid repositioning until adhesive cures (48 hours).

- Slotted & Solid styles for cars & trucks
- Hot design & Styling gives vehicle a new look
- Smoke tint allows brake lights to show through
- Custom Aerodynamic shape for each vehicle
- Helps protect tail light from road debris
- Quick, easy installation with 3M dual-lock
makes product removable at night

CLEANING INSTRUCTIONS: WASH WITH LOTS OF WARM WATER AND A MILD SOAP SOLUTION USING A SOFT, CLEAN CLOTH OR SPONGE. USE OF CLEANERS NOT APPROVED FOR ACRYLIC, OR USE OF IMPROPER SOLVENTS COULD RESULT IN PERMANENT DAMAGE WHICH WILL NOT BE COVERED BY WARRANTY.

WARNING: TAIL LIGHTGUARDS ARE MADE OF BREAKAGE RESISTANT MATERIAL, BUT TO AVOID DAMAGE, MACHINE CAR WASHES ARE NOT ADVISED.

WARNING: For show, competition
& off-road use only, check local
traffic laws before use.

