## **Includes:**

- 1/4 in. and 3/8 in. 72-tooth sealed head ratchets
- 3 in. and 6 in. 1/4 in. extensions
- 3 in., 6in., and 10 in. 3/8 in. extensions
- 1/4 in. and 3/8 in. universal joints
- 3/8 in. F x 1/4 in. M adapter
- 1/4 in. Spinner handle
- 1/4 in. Bit adapter
- (9) 1/4 in. drive SAE 6-point shallow sockets:
  - o 3/16 in. thru 1/2 in.
- (6) 1/4 in. SAE 6-point deep sockets:
  - o 9/32 in. thru 1/2 in.
- (12) 1/4 in. metric 6-point shallow sockets:
  - o 4 mm
  - o 4.5 mm
  - o 5 mm
  - o 5.5 mm
  - o 6 mm thru 13 mm
- (7) 1/4 in. metric 6-point deep sockets:
  - o 5 mm thru 12 mm
- (9) 3/8 in. SAE 12-point shallow sockets:
  - o 3/8 in. thru 7/8 in.
- (6) 3/8 in. SAE 6-point deep sockets:
  - o 9/16 in. thru 7/8 in.
- (2) 3/8 in. SAE spark plug sockets:
  - o 5/8 in.
  - o 13/16 in.
  - (12) 3/8 in. metric 6-point shallow sockets:
    - o 8 mm thru 19 mm
- (10) 3/8 in. metric 6-point deep sockets
  - o 10 mm thru 19 mm
- (2) 3/8 in. metric spark plug sockets:
  - o 14 mm
  - o 18 mm
- (4) 3/8 in. hex bit sockets:
  - o 5/16 in.
  - o 3/8 in.
  - o 8 mm
  - o 10 mm
- (5) tamper-proof Torx bit sockets:
  - o TT-40, TT-45, TT-47, TT-50, TT-55
- Screwdriver bits:
  - o Flat: 1/4, 5/16, 3/8 in.
  - o Phillips: #1, #2, #3
  - o Torx: T-8, T-9, T-10, T-15, T-20, T-25
- High-quality storage case